

PRODUCT
SPECIFICATIONS



The antenna's Trifold® reflector panels are cut from a single-piece of precision spun aluminum.

MilSatCom 4.6 Meter Trifold® Transportable Antenna

The modular 4.6 meter Trifold® transportable design allows one-person deployment in less than 30 minutes.

A broad range of adjustment provides non-critical positioner/trailer orientation and the ability to view geostationary satellites, horizon-to-horizon, from any location worldwide. The antenna's Trifold® reflector panels are cut from a single-piece of precision spun aluminum. Panel design and manufacture provide excellent thermal expansion characteristics and ensure the accurate surface contour. The struts and subreflector are collapsible and store conveniently under the reflector. The 4.6 meter Trifold® transportable antenna is designed for C, X, and Ku-band superior performance specifications.

- U.S. FCC regulation 25-209 for mandatory pattern requirements for 2° satellite spacing. Based on off-satellite measurements at Ku-band.
- ITU-R S.580 and S.465 recommendations for pattern performance for 2° spacing.
- Three axis motorization, tracking and auto acquisition systems are available

SPECIFICATIONS

MilSatCom 4.6 Meter Trifold® Transportable Antenna

Electrical Performance

	C-band 2-Port Linear Pol Feed		C-band 2-Port Circular Pol Feed		X-band 2-Port* Circular Pol Feed		Ku-band 2-Port** Linear Pol Feed		Ku-band 4-Port Linear Pol Feed	
	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency (GHz)	3.625- 4.200	5.850- 6.425	3.625- 4.200	5.850- 6.425	7.250- 7.750	7.900- 8.400	10.950- 12.750	13.750- 14.500	10.950- 12.750	13.750- 14.500
Antenna Gain, dBi	44.10	48.10	44.10	48.00	49.60	50.30	53.70	55.00	53.20	54.70
Antenna Noise Temperature										
10° Elevation	56 K		56 K		56 K		50 K		72 K	
20° Elevation	47 K		47 K		47 K		40 K		62 K	
40° Elevation	44 K		44 K		44 K		37 K		59 K	
Cross Polarization										
On-Axis	30.0 dB	30.0 dB	20.7 dB	27.3 dB	21.3 dB	21.3 dB	35.0 dB	35.0 dB	35.0 dB	35.0 dB
Within 1 dB Beamwidth	28.0 dB	28.0 dB	20.7 dB	27.3 dB	21.3 dB	21.3 dB	27.0 dB	35.0 dB	27.0 dB	35.0 dB
Axial Ratio			1.20 dB	0.75 dB	1.50 dB	1.50 dB				
VSWR Performance	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.35:1	1.25:1	1.35:1	1.35:1
Port-to-Port Isolation										
Rx/Tx (Rx Frequency)	0 dB	30 dB	0 dB	50 dB	0 dB	-110 dB	0 dB	-30 dB	0 dB	-50 dB
Tx/Rx (Tx Frequency)	-85 dB	0 dB	-85 dB	-0 dB	-110 dB	0 dB	-85 dB	0 dB	-85 dB	0 dB
Waveguide Interface Flange	CPR-229 G	CPR-137 G	CPR-229G	CPR-137G	WR-112	WR-112	WR-75	WR-75	WR-75	WR-75
Total Power Handling Capability		2 kW CW		500 W CW		2 kW CW		2 kW CW		1 kW CW

*Includes 110 dB filters

**Includes transmit reflect filter

Mechanical Performance

Optics Type	Dual Reflector, Gregorian
Reflector Material	Precision Formed Aluminum
Reflector Segments	3
Antenna Pointing Range, Course/(Continuous)	Elevation (85°) Azimuth (330°) Polarization (360°)

Environmental Performance

Operational Temperature	40°F to 125°F (-40°C to 50°C)
Wind Loading, Survival	with Motor 125 mph (200 km/h) in Stationary Position without Motor 125 mph (200 km/h) in Stationary Position
Rain	4 in/hr (102 mm/hr)
Solar Radiation	360 BTU/h/ft ² (1135 W/m ²)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and Industrial Areas



ASC Signal Corporation
620 North Greenfield Parkway
Garner, NC 27529 USA

Telephone: +1-919-329-8700

Fax: +1-919-329-8701

Internet: www.ascsignal.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-MGR8

© 2007 ASC Signal Corporation