

PRODUCT  
SPECIFICATIONS

Detail Photos

(on right from top to bottom)

Heavy-duty galvanized Az/El  
Mount

Fine azimuth and elevation  
adjustments

RF tested C-band Linear  
Polarized feed assembly



The reflector is thermoset-  
molded for strength and  
surface accuracy.



## 1.8 m C-band Linear RxTx Class III Antenna System

### TYPE 183

The ASC Signal Type 183 1.8 m Class III RxTx Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of each reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain the critical parabolic shape necessary for transmit performance.

The Az/El mount is constructed from heavy-gauge steel to provide a rigid support to the reflector and feed support arm. Heavy-duty lockdown bolts secure the mount to any 114 mm (4.50") O.D. mast and prevent slippage in high winds. Hot-dip galvanizing is standard on this model for maximum environmental protection.

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece precision offset thermoset-molded reflector.
- Heavy-duty galvanized Az/El mount.
- Fine Azimuth and elevation adjustments.
- Galvanized support arm and alignment struts.
- Factory pre-assembled mount.
- Galvanized and stainless hardware for maximum corrosion resistance.
- RF tested feed assembly.
- Heavy-duty Class III mount for 11 kg (25 lb) RF electronics (LNB & BUC).

## SPECIFICATIONS

### Type 183 1.8 m C-band Linear RxTx Class III Antenna System

#### RF Performance

		C-band Linear
Effective Aperture		1.8 m (71 in)
Operating Frequency	Tx	5.850 - 6.725 GHz
	Rx	3.400 - 4.200 GHz
Polarization		Linear, Orthogonal
Gain ( $\pm 3$ dBi)	Tx	39.3 dBi @ 6.1 GHz
	Rx	35.4 dBi @ 3.9 GHz
3 dB Beamwidth	Tx	2.0° @ 6.1 GHz
	Rx	3.0° @ 3.9 GHz
Sidelobe Envelope (Tx, Co-Pol dBi)	2.5° < $\Theta$ < 20°	29 - 25 Log $\Theta$
	20° < $\Theta$ < 26.3°	-3.5
	26.3° < $\Theta$ < 48°	32 - 25 Log $\Theta$
	48° < $\Theta$ < 180°	-10
Antenna Cross-Polarization		30 dB on Axis
Antenna Noise Temperature	10° El	41° K
	20° El	36° K
	30° El	33° K
VSWR	Tx	1.3:1
	Rx	1.5:1
Isolation (Port to Port)	Tx	60 dB
	Rx	60 dB
Feed Interface	Tx	Type N or CPR-137
	Rx	CPR-229

(All specifications typical)

#### Mechanical Performance

Reflector Material		Glass Fiber Reinforced Polyester
Antenna Optics		One-Piece Offset Feed Prime Focus
Mount Type		Elevation over Azimuth
Elevation Adjustment Range		10° - 90° Continuous Fine Adjustment
Azimuth Adjustment Range		360° Continuous $\pm 12'$ Fine Adjustment
Mast Pipe Interface		114 mm (4.50 in) Diameter
Wind Loading	Operational	80 km/h (50 mph)
	Survival	200 km/h (125 mph)
Temperature		-50°C to 80°C
Humidity		0 to 100% (Condensing)
Atmosphere		Standard Hardware Meets 500 Hour Salt Spray Test Requirements (ASTM B-117)
Solar Radiation		360 BTU/h/ft <sup>2</sup>
Shock and Vibration		As Encountered During Shipping and Handling



ASC Signal Corporation  
1315 Industrial Park Drive  
Smithfield, NC 27577  
USA

Telephone: +1-919-934-9711

Internet: [www.ascsignal.com](http://www.ascsignal.com)

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-VSAT33.1

© 2007 ASC Signal Corporation